



MM COMMODITIES

PRODUCT RANGE

BASIC PVC FLAT CABLES TO BS4804



6280YH size: 1, 1.5 mm², Grey sheath

6290YH size: 1.5 to 16 mm², Grey sheath

6290YH size: 1, 1.5 mm², Twin Brown, Grey sheath

6290YH size: 1, 1.5 mm², Red sheath

6290YH size: 1, 1.5 mm², Grey sheath

BASIC LSHF FLAT CABLES TO BS7211



6291SH size: 1.5 mm², White sheath

6293SH size: 1.5 to 16 mm², White sheath

6293SH size: 1.5 mm², White sheath

BASIC DOUBLE INSULATED SINGLE CORE CABLES TO BS4804 & BS7211



6180YH size: 1 to 35 mm², Grey sheath

6180YH size: 50 to 400 mm², Black sheath

BASIC PVC & LSHF (LSF) INSULATED NON-SHEATHED CABLES HETV-R BS4804 & HETZ-R BS7211



6491X size: 1.5 to 400 mm², available in Blue, Brown, Grey, Black, Green-Yellow

6491B size: 1.5 to 400 mm², available in Blue, Brown, Grey, Black, Green-Yellow

TRI-RATED NON-SHEATHED FLEXIBLES TO UL, CSA and BS6231



Ts-002 size: 1.5 to 16 mm², available in Blue, Brown, Grey, Black, Green-Yellow

►HAR► PVC INSULATED LIGHT DUTY FLEXIBLE CORD TO H03VVH2-F (BS6800) & H03VVY2 (BS6800) 380/380V



2180Y size: 0.5, 0.75 mm², White or Black sheath

2180Y size: 0.5, 0.75 mm², White, Black, Orange sheath

2180Y size: 0.5, 0.75 mm², White, Black, Orange sheath

2180Y size: 0.5, 0.75 mm², White sheath

2180Y size: 0.5, 0.75 mm², White sheath

►HAR► PVC INSULATED NORMAL DUTY FLEXIBLE CORD TO H03VVH2-F (BS6800) H03VVY-F (BS6800)



2180Y size: 0.75 to 2.5 mm², White, Black sheath

2180Y size: 0.75 to 2.5 mm², White, Black, Orange sheath

2180Y size: 0.75 to 2.5 mm², White, Black, Orange sheath

2180Y size: 0.75, 2.5 mm², White or Black sheath

2180Y size: 0.75, 2.5 mm², White or Black sheath

2180Y size: 0.75, 2.5 mm², White sheath

►HAR► LSHF INSULATED NORMAL DUTY FLEXIBLE CORD TO H03Z121 380/380V



3180B size: 0.75 to 2.5 mm², White sheath

PVC INSULATED -40 °C ARCTIC GRADE 380/380V FLEXIBLE CORD TO H03VV-F (BS6800-F) HAR approved and BASIC certification in progress



3180A size: 0.75 to 2.5 mm², Yellow or Blue sheath

3180A size: 0.75 to 4 mm², Yellow or Blue sheath

►HAR► PVC INSULATED 90 °C HEAT RESISTING FLEXIBLE CORD TO H03VV2-F (BS6800) 380/380V



3080Y size: 0.5 to 2.5 mm², White sheath

TELEPHONE CABLES TO BT CW1308 ALARM PLUX TO BS4737



Telephone: 1 to 10 pair, White sheath

Alarm: 4 to 12 cores, White sheath

DATA 4-PAIR CAT 5E & PATCH CABLE



Available in 1000ft (305m) length

PVC 4-pair UTP-Cat5E, Grey sheath

4-pair UTP-Cat5E, Blue sheath

LSF 4-pair UTP-Cat5E, Violet sheath

4-pair UTP-Cat5E, Blue sheath

TV DOWNLOAD, SATELLITE & DIGITAL SATELITE



TV Low Loss White & Brown

RG6 Copper Braided/Mil-H 38812, Black or White sheath

Digital Satellite (Type 100) CAT and DROTAI specification Black or White sheath

BASIC & LPCB FIRE RATED SWA BS 7546-F2 HALOGEN FREE



1.5 mm², 304 Core, Red & White sheath

2.5 mm², 304 Core, Red & White sheath

CONTROL CABLE CY, SY & YY TO IEC 21.13 CENELEC member approved



CY size: 0.75 to 2.5 mm², Cores 2/3/4/5/7/12/18

SY size: 0.75 to 6 mm², Cores 2/3/4/5/7/12/18

YY size: 0.75 to 6 mm², Cores 2/3/4/5/7/12/18

PVC LOW VOLTAGE



1280W Bell Wire, White, in 100m

Speaker Cable 12, 42, 70 strands, White with black marker, Low Voltage Lighting Cable size 2x10mm², Black

►HAR► RUBBER FLEXIBLE CORD



H05RH-F T100/3100 & 3100 size: 0.75 to 2.5 mm², Black

H05RH-F TQ 3100TQ & 3104TQ size: 0.75 to 1.5 mm², White

H05RH-F TQ 3105TQ & 3104TQ size: 1.5 to 2.5 mm², White

H05RH-F 3105TQ size: 25 to 300 mm², Black

H05RH-F 3102/3145P size: 1.0 to 25 mm², Black

Welding 3105H size: 10 to 120 mm²

BASIC XLPD/PVC & XLPDLSH/SWA BS 5467 & BS6724



6941X, RWA size: 120 to 630 mm²

6942/3/4/5, DWA size: 1.5 to 400 mm²

6943, 6942/5/6 size: 1.5, 2.5 mm²

6941B, RWA size: 120 to 630 mm²

6942/3/4, DWA size: 1.5 to 400 mm²

6946, SWA size: 1.5 to 30 mm²

6947 to 6942/5/6 size: 1.5, 2.5 mm²

BASIC & LPCB FIRE RATED SWA BS 7546-F2



6942/5/7, size: 1.5 to 120 mm²

MM Commodities

Unit 08, Dungarvan Business Park

Dungarvan

Co Waterford

Republic of Ireland

Eircode: X35 TX03

Website: www.mmcommodities.ie

Email: info@mmcommodities.ie

Tel: +353 (0)568 5184